

# Roalux Wall Putty

Interior  Exterior **RCP**

## Product Description

Roalux Wall Putty is exclusive product based on White Cement, re-dispersible polymer and functional additives for application on exterior & interior rough plasters to give a smooth finish.



## Features & Benefits

- Good Workability
- Good compressive strength
- Finish : MATT
- Washability : NO

## Colors

White

## Packing

1KG
 5KG
 20KG
 40KG
 Polyether Pouch

## Recommended Uses

<b>AREA</b> <input checked="" type="checkbox"/> Interior <input checked="" type="checkbox"/> Exterior	<b>SURFACES</b> <ul style="list-style-type: none"> <li>■ Cement Plasters</li> <li>■ Asbestos Sheets</li> <li>■ Concrete</li> <li>■ Brickwork, Etc.,</li> </ul>	<b>2 COATS</b> <b>18 - 20</b> SQFT/KG
----------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------

## Application Details & Surface Preparation

<b>Tools</b>  Putty Blade	<b>Mixing</b>  Mix well before use	<b>Coverage</b>  20 - 25 sqft*	<b>Thining &amp; Ratio</b> Water 30-35% by Weight Add water to putty Mixing fine past it format	<b>Dry Timing</b>  Surface Dry 20 Min
<b>Cleaning</b>  Clean surface loose paint, dust with emery Paper Wipe clean soft cloth	<b>Environment</b>  Temp : 10-40 Dgr. Humi : Below 80%	<b>Surface</b>  Sprinkle the surface with water	<b>Application</b>  First Coat Allow to dry 4-5 hrs. Second Coat Allow to dry 10-12 hrs Coating thickness should not exceed 1.5mm	<b>Safety</b>  Non- flammable No added Lead Mercury / Chromium

\* Practical spreading rate will vary from the quoted Theoretical spreading rate due to factors such as method and condition of application as well as surface roughness.