

Roalux Weather Shine Emulsion

Interior Exterior **RWS**

Product Description

Roalux weather shine emulsion performs like all season paints. It gives smooth and shine to the exterior surface with good alkali resistance and fungal uv resistance, hydro phobic and elegant looks.



Features & Benefits

- Weather Guard
- Anti Fungal
- Finish : SHEEN
- Washability : HIGH

Colors

White & bases for Roalux Fandek Colors.

Packing



Plastic Pails

Recommended Uses

AREA <input type="checkbox"/> Interior <input checked="" type="checkbox"/> Exterior	SURFACES <ul style="list-style-type: none"> ■ Concrete, Walls ■ Masonary Surface 	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> 1st COAT 130 - 140 SQFT/LT </div> <div style="text-align: center;"> 2nd COAT 80 - 90 SQFT/LT </div> </div>
---	--	--

Application Details & Surface Preparation

Tools Brush, Roller & spray	Mixing Shake well before use	Coverage 120 - 140 sqft*/single coat	Thining & Ratio Water 40-50% 40-50% Volume	Dry Timing Surface dry in 30 min
Cleaning Clean surface loose paint, dust with emery Paper Wipe clean soft cloth	Environment Temp : 10-40 Dgr. Humi : Below 80%	Surface Seal cracks with 1:3 cement & sand. Thining 1Lr of Primer 1Lr of water	Application Apply 2 coats of RWS with 400-500ml of water. 3 coats are recommended.	Safety Non- flammable No added Lead Mercury / Chromium

* Practical spreading rate will vary from the quoted Theoretical spreading rate due to factors such as method and condition of application as well as surface roughness.